

## H.264 Network DVR ::



### DVR804

- ◆ **H.264 hardware-based codec**
- ◆ **Triplex Function (Simultaneously playback, record and remote viewer)**
- ◆ **Adjustable recording resolution (D1, Half D1 and CIF)**
- ◆ **4 Audio In/ 1 Audio Out**
- ◆ **Various recording setup**
- ◆ **PTZ/ Alarm Support**
- ◆ **Mobile Surveillance Support**

## SPECIFICATION

### MONITORING

Video Input	Composite: 4 x BNC	Composite: 8 x BNC
Video Output	1X CRT, 1 x VGA 1X CRT, 1 x VGA	
Display Resolution	720 x 480 / 720 x 576	
Display Rate	Real-Time 120 / 100 IPS in Total	Real-Time 240 / 200 IPS in Total
Features	4-Split, Sequencing (SEQ)	9-Split, Sequencing (SEQ)

### RECORDING & PLAYBACK

Compression	H.264 Hardware-Based Codec	
Recording Resolution/ Rate (Adjustable)	720x480 or 720x576 up to 60 or 50 IPS 720x240 or 720x288 up to 120 or 100 IPS 360x240 or 352x288 up to 120 or 100 IPS	720x480 or 720x576 up to 60 or 50 IPS 720x240 or 720x288 up to 120 or 100 IPS 360x240 or 352x288 up to 240 or 200 IPS
Recording Quality	4 x Levels (High/ Best/ Normal/ Low)	
Playback Rate	720x480 or 720x576 up to 60 or 50 IPS 720x240 or 720x288 up to 120 or 100 IPS 360x240 or 352x288 up to 120 or 100 IPS	720x480 or 720x576 up to 60 or 50 IPS 720x240 or 720x288 up to 120 or 100 IPS 360x240 or 352x288 up to 240 or 200 IPS
Recording Mode	Emergency (Manual), Scheduled (Round-the-Clock [RTC], Alarm)	
Search Mode	Date/Time, Event (Motion, Alarm, Video Loss)	
Features	Video Motion Detection (VMD), Privacy Recording, Digital Zoom (2X)	

### SYSTEM

Languages	Multi-Language Support (English, Japanese, Chinese etc.)
Storage	1 x SATA HDD Slot
Data Export Medium	1 x USB 2.0 Slot
HDD Management	Status, Format, Overwrite, Capacity Warning, HDD Smart Information
Features	Firmware Upgrade (USB FlashDrive)

### NETWORK

Connection	1 x RJ-45 Ethernet
Protocols	PPPoE/ Static/ DHCP IP & DDNS
Remote Software	Management, Monitoring, Recording, Playback, PTZ, Event Search
Network Data Export	Backup, AVI

### INTEGRATION

Audio In/Out	4 x RCA In, 1 x RCA Out
Alarm In/Out	2 x In (NO / NC Switchable), 2 x Out (NO / NC)
PTZ Control Protocols	1 x RS-485 (Pelco D, Pelco P, etc)
User Interface	On Screen Display, Front Panel Buttons , IR Remote Control *, USB Mouse

### OTHER

Dimensions (W x H x D)	280 x 260 x 80 mm
Unit Weight	1.0 kg (without HDD)
Operating Temperature	0 ~ 45 °C
Operating Humidity	0 ~ 90%
Power	DC 12C, 4.16 A Adaptor
Approvals	CE, FCC, RoHS, WEEE